

MATERIAL SAFETY DATA SHEET

Date Prepared: 6/11/04
Finishing Glaze

Page: 1
MSDS Number: 110001

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: Finishing Glaze
Product Numbers: 100044 and 1000045
Product Use: Automotive Glazing Compound

Company

Fibre Glass-Evercoat
a Division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, Ohio USA
Phone: 513-489-7600

Emergency Telephone Numbers:

CHEMTREC: 1-800-424-9300
CANUTEC: 1-613-996-6666

Prepared By: Safety Department

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredient(s) | CAS Number | EINECS Number | % (by weight) |
|-------------------|------------|---------------|---------------|
| Water | 7732-18-5 | 231-791-2 | 60 - 70 |
| Petroleum Naphtha | 64742-48-9 | 265-150-3 | 10 - 15 |
| Clay | 66402-68-4 | 266-340-9 | 1 - 10 |
| Light Petroleum | 64742-47-8 | 265-149-8 | 1 - 5 |

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

SECTION 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER! COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL OR FATAL IF SWALLOWED.

Potential Health Effects

Acute Effects (Short Term):

Eye: Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.

Skin: May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

Swallowing: Ingestion of this material may cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Aspiration of this material into the lungs due to vomiting may produce chemical pneumonitis which can be fatal.

Inhalation: Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache, and dizziness. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

MATERIAL SAFETY DATA SHEET

Date Prepared: 6/11/04

Page: 2

Finishing Glaze

MSDS Number: 110001

Chronic Effects of Overexposure (Long Term):

Petroleum Distillates: The substance may cause effects on the central nervous system.

Cancer Information: No information available.

Other Health Effects: NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Primary Route(s) of Entry: Inhalation, Skin contact, Eye contact, Ingestion, Skin absorption.

SECTION 4. FIRST AID MEASURES

- Eyes:** Flush eyes gently with water for at least 15 minutes. Seek immediate medical attention.
- Skin:** Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.
- Swallowing:** Consult a physician or poison control center immediately. DO NOT INDUCE VOMITING. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. If possible, do not leave individual unattended.
- Inhalation:** If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel.

SECTION 5. FIRE FIGHTING MEASURES

Flash Point: 122 °F (50 °C)

Explosive Limit: Lower: 0.6% **Upper:** 13.5%

Autoignition Temperature: 428.0 °F (220.0 °C)

OSHA Flammability Class: Combustible Liquid – Class II

Hazardous Products of Combustion: May form: carbon dioxide, carbon monoxide and various hydrocarbons.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

MATERIAL SAFETY DATA SHEET

Date Prepared: 6/11/04
Finishing Glaze

Page: 3
MSDS Number: 110001

Extinguishing Media: Regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions: Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus NIOSH approved with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

NFPA Rating: Health - 1, Flammability - 2, Reactivity - 0

SECTION 6. ACCIDENTAL RELEASE MEASURES

In Case of Spill: Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate the area. Wear proper protective equipment (Section 8). Avoid breathing vapors. Collect with an inert absorbant and dispose of properly.

SECTION 7. HANDLING AND STORAGE

Handling: All hazard precautions given in the data sheet must be observed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only with adequate ventilation. Do not breathe airborne particulate, dust or vapors. Do not take internally. Close container after each use. **Keep out of reach of children.**

Storage: Store material in a cool, well-ventilated area. For maximum product quality, avoid prolonged storage at temperatures above 75°F (25°C). Do not use or store near heat, sparks, or open flame. Keep container tightly closed. Protect from freezing. Avoid contact with incompatible materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are recommended.

Skin Protection: Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. A barrier cream may be used for additional skin protection. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors. A respirator may be necessary during and after application and while cleaning pads.

MATERIAL SAFETY DATA SHEET

Date Prepared: 6/11/04

Page: 4

Finishing Glaze

MSDS Number: 110001

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below acceptable limits.
Explosion-proof ventilation system is acceptable.

Exposure Guidelines:

None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--|-----------------------------------|--|-------------------|
| Boiling Point: | 212 °F / 100 °C (Water) | Vapor Density: | Heavier than air. |
| Specific Gravity / Density: | 0.955 / 7.95 lbs/gal | Percent Volatiles by weight: | 70 – 90 % |
| Evaporation Rate: | Slower than ethyl ether. | Physical State: | Liquid |
| Melting Point: | 32 °F / 0 °C (Water) | pH: | 8.0 – 9.0 |
| Odor: | Sharp, aromatic odor. | Solubility: | Soluble in water. |
| Vapor Pressure: | 17.5 mmHg @ 68 °F / 20 °C (Water) | Appearance: | Gray Liquid |
| Octanol/Water Partition Coefficient: | Unknown | VOC (as packaged-less exempts and water): | 15 % by weight |
| VHAP Content by weight – as packaged: | 0% | | |

SECTION 10. STABILITY AND REACTIVITY

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: May form: carbon dioxide, carbon monoxide and various hydrocarbons.

Chemical Stability: Stable under normal handling conditions.

Incompatibility: Avoid contact in uncontrolled conditions with: strong oxidizing agents and water-reactive materials.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity Data: No information available.

Carcinogenicity: See Cancer Information, Section 3.

Mutagenicity: No significant evidence found.

Teratogenicity: No significant risk of birth defects or reproductive toxicity to humans.

MATERIAL SAFETY DATA SHEET

Date Prepared: 6/11/04

Finishing Glaze

Page: 5

MSDS Number: 110001

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: This product is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.

SECTION 13. DISPOSAL CONSIDERATION

RCRA Hazardous Waste: This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261). Dispose of in accordance with applicable federal, state, and local regulations.

RCRA Hazard Class: This material would be regulated as EPA Hazardous Waste Number D001 based on the characteristic of ignitability.

SECTION 14. TRANSPORT INFORMATION

DOT Description: The DOT Classification for shipping is dependant on quantity, type of packaging (a kit may include other components), or method of shipment.

SECTION 15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (USA) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

None

SARA Title III: Section 302- Extremely Hazardous Substances

None

SARA Title III: Section 313- Toxic Chemical List

None

International Regulations

EINECS (Europe) The intentional ingredients of this product are listed.

DSL (Canada) The intentional ingredients of this product are listed.

WHMIS Classification

Health Hazard: D2B (Other Toxic Effects)

Physical Hazard: B3 (Combustible)

MATERIAL SAFETY DATA SHEET

Date Prepared: 6/11/04
Finishing Glaze

Page: 6
MSDS Number: 110001

State and Local Regulations

California Proposition 65:

This product contains the following chemical(s) known to the state of California to cause cancer. Ethyl Acrylate

This product contains the following chemical(s) known to the state of California to cause birth defects or reproductive harm. Ethylene Glycol Monomethyl Ether

SECTION 16. OTHER INFORMATION

HMIS Rating: Health – 1*, Flammability - 2, Reactivity - 0
Key- 0=Least, 1=Slight, 2=Moderate, 3=Serious, 4=Extreme, *=Chronic Effects

Additional Information may be obtained by calling the Evercoat MSDS Hotline at 1-800-729-7600.

NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances.