

Glycol

MATERIAL SAFETY DATA SHEET

Updated MSDS



Date Issued: 02/28/2005
 MSDS No: ICC-02169
 Date-Revised: 03/04/2010
 Revision No: 5

INTERCOOL P-300 30/70**I. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: INTERCOOL P-300 30/70
GENERAL USE: Heat Transfer Fluid
PRODUCT DESCRIPTION: Propylene glycol based heat transfer fluid
PRODUCT FORMULATION NAME: INTERCOOL P-300 30/70
CHEMICAL FAMILY: Glycol
ACTIVE INGREDIENT(S): Propylene Glycol

24 HR. EMERGENCY TELEPHONE NUMBERS

800-ICC-CHEM

MANUFACTURER

Interstate Chemical Company, Inc.
 Corporate Headquarters-Hermitage
 2797 Freedland Road
 Hermitage PA 16148
Emergency Contact: F. James Corbett, Director
 of Quality & EH&S
Product Stewardship: 800-422-2436
Alternate Emergency Phone: 724-981-3771
Transportation: 800-422-2436
Alternate Transportation Phone: 724-981-
 3771
Service Number: 800-422-2436
Alternate Customer Service: 724-981-3771

COMMENTS: This product contains propylene glycol which is on the FDA's GRAS (GENERALLY REGARDED AS SAFE) list. Dispose of in accordance with all applicable local, state, and federal regulations. For assistance with your waste management/environmental service needs including waste disposal and recycling, please contact Interstate Chemical Environmental Services at 800-422-2436 ext. 1703 or email us at environmentalservices@interstatechemical.com

II. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

PHYSICAL APPEARANCE: Substance may cause skin and eye irritation.

IMMEDIATE CONCERNS: Irritating to eyes, respiratory system and skin.

POTENTIAL HEALTH EFFECTS

EYES: May cause irritation.

SKIN: Minor skin irritation and penetration may occur.

INGESTION: Relatively non-toxic. Ingestion of sizable amount (over 100ml) may cause some gastrointestinal upset and temporary central nervous system depression. Effects appear more severe in individuals with kidney problems

INHALATION: Vapor inhalation is generally not a problem unless heated or misted.

INTERCOOL P-300 30/70

Page 2 of 5

4. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS	EINECS
Propylene Glycol	~ 30	57-55-6	
Corrosion Inhibitors and Buffers	< 10	mixture	
Yellow Dye	< 1	6417-85-2	
Deionized Water	~ 70	7732-18-5	231-791-2

5. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Remove contaminated clothing. Wash with soap and water. Get medical attention.

INGESTION: Not expected to require first aid measures. Give several glasses of water to drink to dilute. If large amounts were swallowed, get medical advice.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

6. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: Not Flammable

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

OTHER CONSIDERATIONS: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Move exposed containers from fire area, if it can be done without risk. Use water to keep fire-exposed containers cool.

7. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid and place in sealed container for disposal.

LARGE SPILL: Ventilate area of leak or spill. Remove all sources of ignition. Contain and recover liquid when possible. Do not flush to sewer.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: When released into water, this material is expected to readily biodegrade.

LAND SPILL: When released into the soil, this material is expected to readily biodegrade.

AIR SPILL: When released into the air, this material is expected to have a half-life between 1 and 10 days.

GENERAL PROCEDURES: Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer!

8. HANDLING AND STORAGE

GENERAL PROCEDURES: Protect container from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture, and incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

HANDLING: Store in adequate storage area at ambient temp.

STORAGE: Store in a cool dry place. Keep from freezing.

STORAGE TEMPERATURE: (20°F) Minimum to (150°F) Maximum

LOADING TEMPERATURE: (20°F) Minimum to (150°F) Maximum

LOADING/UNLOADING VISCOSITY: No information found

SHELF LIFE: Greater than one year when stored in its original container at the recommended storage temperature with the bungs closed.

4. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) and a face shield.

SKIN: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or frequently repeated contact could occur, use chemical protective clothing made from butyl rubber. Selection of specific items such as gloves, boots, apron, full-body suit, etc. will depend on local operation.

RESPIRATORY: For most conditions, no respiratory protection should be needed, however, in dusty atmospheres, use a NIOSH approved dust respirator.

PROTECTIVE CLOTHING: Where splashing is possible, full chemically resistant protective clothing and boots may be required.

WORK HYGIENIC PRACTICES: Establish good personal hygiene and work practices. Always wash hands and face before eating, drinking or smoking. Provide safety shower and eye wash station in work area.

OTHER USE PRECAUTIONS: If the exposure limit is exceeded, a half-face respirator with an organic vapor cartridge and particulate filter (NIOSH type P95 or R95 filter) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece respirator with an organic vapor cartridge and particulate filter (NIOSH P100 or R100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. Please note that N series filters are not recommended for this material. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

5. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Odorless

APPEARANCE: Clear, yellow liquid.

COLOR: Fluorescent yellow

INTERCOOL P-300 30/70

Page 4 of 5

pH: 8.0 to 9.5**PERCENT VOLATILE:** Not Determined**VAPOR PRESSURE:** ~ 7 mmHg at (60°F)**VAPOR DENSITY:** > 1 (Air=1)**BOILING POINT:** (214°F) Boiling Point Chart**FREEZING POINT:** (9°F) Freezing Point Chart**FLASHPOINT AND METHOD:** Not Flammable**SOLUBILITY IN WATER:** Completely Miscible**EVAPORATION RATE:** < 1 (n-Butyl Acetate=1)**DENSITY:** 8.59 lbs/gal at (60°F)**SPECIFIC GRAVITY:** 1.030 (water=1) at 20°C**VISCOSITY #1:** ~ 8 Centipoise at (68°F)**(VOC):** ~ 30.000 % by volume Calculated**WEIGHT PER VOLUME:** 8.59 lbs/gal**10. STABILITY AND REACTIVITY****STABLE:** Yes**HAZARDOUS POLYMERIZATION:** No**CONDITIONS TO AVOID:** Oxidizing materials.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon dioxide and carbon monoxide may form when heated to decomposition. Aldehydes or lactic, pyruvic or acetic acids may also be formed.**INCOMPATIBLE MATERIALS:** Heat, flames, ignition sources and incompatibles.**11. TOXICOLOGICAL INFORMATION****GENERAL COMMENTS:** Oral rat LD50: 20g/kg. Skin rabbit LD50: 20.8g/kg. Irritation: Eye rabbit/Draize, 500 mg/24H mild.**12. ECOLOGICAL INFORMATION****CHEMICAL FATE INFORMATION:** When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into water, this material is expected to readily biodegrade. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life between 1 and 10 days.**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility.**EMPTY CONTAINER:** Dispose of container and unused contents in accordance with federal, state and

local requirements.

4. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated by DOT

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not regulated

5. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** No

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: This material is listed on the EPA TSCA Inventory of Chemical Substances

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Not listed on the toxic substances in schedule 1 of the Canadian Environmental Protection Act, 1999 (CEPA 1999).

6. OTHER INFORMATION

REASON FOR ISSUE: Revised MSDS

APPROVED BY: F. James Corbett **TITLE:** Director of Quality & EH&S

PREPARED BY: F. James Corbett


INFORMATION CONTACT: 800-422-2436 x 1136

REVISION SUMMARY: Revision #: 5. This MSDS replaces the June 16, 2008 MSDS. Any changes in information are as follows: In Section 1: Approved by, Title, Information Contact, MSDS Product Code, MSDS Classification In Section 8: Skin Protection, Eyes-Face Protection, Respiratory Protection, Work Hygienic Practices, Clothing Protection

HMS RATING

HEALTH HAZARD:	0
ENVIRONMENTAL HAZARD:	0
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	B

NFPA CODES



MANUFACTURER DISCLAIMER: Interstate Chemical Company, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.